



DIAMOND DISC SEGMENTS REINFORCED CONCRETE, STEEL

EXPERT

HIGH EFFICIENCY AND DURABILITY

- Laser welded segments diamond disc.
- Body with special ventilation holes for better cooling.
- Good cutting speed and durability.
- Mounted on M14 aluminum flange or bore 22,23.
- Trou d'ergot 1/12/57 sur disque alésage 25,4 de Ø 300



MASONRY












REINFORCED CONCRETE,
CONCRETE, CONCRETE
BLOCK, SOLID BRICK,
NATURAL STONE, GRANITE,
STEEL



SPECIFICATIONS:

| REF | | | | | | | | | | | |
|------------|------------------------|-------|-------|---------------------|------------|--------------------|-------------------------------------|---------|-------------|-------------------|--|
| 720115 | 1 | 115 | 13300 | 22,23 | 2,4 | 34 | 10 | 8 | A sec | 3661589 004567 | |
| 720125 | 1 | 125 | 12250 | 22,23 | 2,4 | 32 | 10 | 9 | A sec | 3661589 004574 | |
| 720230 | 1 | 230 | 6650 | 22,23 | 2,6 | 38 | 10 | 16 | A sec | 3661589 004581 | |
| 720236 | 1 | 230 | 6650 | M14 | 2,6 | 38 | 10 | 16 | A sec | 3661589 081179 | |
| 720301 | 1 | 300 | 6400 | 20 | 3,0 | 40 | 10 | 20 | - | 3661589 004062 | |
| 720305 | 1 | 300 | 6400 | 25,4/22,2 | 3,0 | 40 | 10 | 20 | - | 3661589 | |
| SOLID WOOD | WOOD-DERIVED PANELS | METAL | TILE | CONCRETE MASONRY | STONE TILE | MULTI MATERIALS | PLASTER & AMP; SOFT MATERIALS | ASPHALT | ACCESSORIES | | |

| REF |  |  |  |  |  |  |  |  | |  |
|--------|---|---|---|---|---|---|---|---|---|---|
| 720351 | 1 | 350 | 5500 | 20 | 3,2 | 40 | 10 | 24 | - | 3661589 004093 |
| 720355 | 1 | 350 | 5500 | 25,4 | 3,2 | 40 | 10 | 24 | - | 3661589 004109 |
| 720405 | 1 | 400 | 4800 | 25,4 | 3,2 | 38 | 10 | 28 | - | 3661589 004116 |

SOLID WOOD

WOOD-DERIVED
PANELS

METAL

TILE

CONCRETE
MASONRY

STONE TILE

MULTI
MATERIALS

PLASTER & AMP;
SOFT
MATERIALS

ASPHALT

ACCESSORIES