

VERTICAL LOG SPLITTER 12 T

LOG SPLITTER

- 2-handle control device for safe working.
- Arms on each side of the machine to hold the log after the splitting operation.
- PTO connection (optional shaft connector, not supplied).
- PTO connection (optional shaft connector, not supplied).
- 2 wheels Ø 230 mm for easy moving.
- Automatic return of the splitting wedge with safety stop.
- Highly efficient hydraulic pump.
- Log lifting arm controlled by the hydraulic system.



SOLID WOOD

WOOD-DERIVED
PANELS

METAL

TILE

CONCRETE
MASONRY


STONE TILE

MULTI
MATERIALS

PLASTER &
SOFT
MATERIALS

ASPHALT

ACCESSORIES

RÉF	LOFEV120
Conditionnement	1
Colisage	1105 x 665 x 2150 mm
Garantie	24
Poids net	182 kg
Poids brut	195 kg
Encombrement machine montee	1200 x 1200 x 2525 mm
Reference pour pieces detachees	310700 (+ N°/ vue éclatée)
Entrainement	Cardan
Vitesse de rotation cardan	540 t/min
Puissance tracteur mini	12 kW / 16 CV
Puissance de fendage	12 Tonnes
Vitesse de fendage	5 à 24 cm/s
Vitesse de remontée du coin	7 cm/s
Diamètre de bûche maxi	Ø 400 mm
Longueur de bûche maxi	1000 mm
Pression hydraulique	24 Mpa
Capacité du réservoir / Totale	5,4 L / 8,0 L
Type d'huile	HLP46
Puissance Acoustique LwA	97 dB(A) à vide
	3661589119520

SOLID WOOD

WOOD-DERIVED
PANELS

METAL

TILE

CONCRETE
MASONRY

STONE TILE

MULTI
MATERIALS

PLASTER &
SOFT
MATERIALS

ASPHALT

ACCESSORIES

ACCESSOIRES

301001



**PTO shaft
connector
T4-900mm**

SOLID WOOD

WOOD-DERIVED
PANELS

METAL

TILE

CONCRETE
MASONRY

STONE TILE

MULTI
MATERIALS

PLASTER & AMP;
SOFT
MATERIALS

ASPHALT

ACCESSORIES