


BANDSAW WITH STAND AND PEDAL WHEEL KIT 355 MM

BAND SAW

- Mechanically welded frame, rigid and strong.
- 45° tilting cast iron sawing table with upper and lower trunnions in die-cast aluminum.
- Upper and lower blade guides with 3 cheeks.
- Blade upper guide mounted on a rack and adjustable in height by a crank.
- Quick release blade tension lever.
- 2 cutting speeds by changing the position of the belt, depending on the material to be cut.
- 2 cutting speeds by changing the position of the belt, depending on the material to be cut.
- Rip fence with graduation can be positioned on the left of the blade.
- Safety switch on each door.
- Safety switch on each door.



Balanced cast iron flywheels



Guide de lame supérieur et inférieur à galets



Table tilting at 45°

SOLID WOOD

WOOD-DERIVED
PANELS

METAL

TILE

CONCRETE
MASONRY


STONE TILE

MULTI
MATERIALS

PLASTER &
SOFT
MATERIALS

ASPHALT

ACCESSORIES

RÉF	SRU356
Conditionnement	1
Colisage	1300 x 460 x 590 mm
Garantie	24
Poids net	100 kg
Poids brut	110 kg
Encombrement machine montee	850 x 770 x 1800 mm
Reference pour pieces detachees	110600 (+ N°/ vue éclatée)
Puissance moteur (230 V - 50 Hz)	1450 W - S1
Col de cygne	345 mm
Hauteur de coupe maximale	235 mm
Dimensions de la lame	2630 x 6 - 20 mm
Dimensions de la table Scie	548 x 400 mm
Inclinaison de la table	De 0° à 45°
Hauteur de travail	1040 mm
Diamètre des volants	350 mm
Vitesse de coupe	440 - 900 m/min
Nombre de vitesses	2
Guide d'onglet	± 60°
Diamètre sortie d'aspiration	Ø 100 mm
	3700501703383

SOLID WOOD

WOOD-DERIVED
PANELS

METAL

TILE

CONCRETE
MASONRY

STONE TILE

MULTI
MATERIALS

PLASTER & SOFT
MATERIALS

ASPHALT

ACCESSORIES