

PINCE DE SERRAGE ER 32 - Ø MINI 2 MM - Ø MAXI 20 MM

ACCESSORIES



EXPERT

- Pincas de serrage pour mandrin de défonceuse C.N.C.
- Pincas en acier traité, rectifiées : doivent être mises en place avec la plus grande attention.
- Tolérance de serrage de 0,5 mm inférieur au diamètre (0,7 mm pour les diamètres de 18 à 20 mm).

SPECIFICATIONS:

REF				
890.032.003	1	33 / 3	40	3510785 412495
890.032.004	1	33 / 4	40	3510785 412501
890.032.005	1	33 / 5	40	3510785 412518
890.032.006	1	33 / 6	40	3510785 412525
890.032.008	1	33 / 8	40	3510785 412549
890.032.010	1	33 / 10	40	3510785 412563

SOLID WOOD

WOOD-DERIVED
PANELS

METAL

TILE

CONCRETE
MASONRY



STONE TILE

MULTI
MATERIALS

PLASTER &
SOFT
MATERIALS

ASPHALT

ACCESSORIES

REF				
890.032.012	1	33 / 12	40	3510785 412570
890.032.014	1	33 / 14	40	3510785 412594
890.032.016	1	33 / 16	40	3510785 412617
890.032.018	1	33 / 18	40	3510785 412624
890.032.020	1	33 / 20	40	3510785 412648

SOLID WOOD

WOOD-DERIVED
PANELS

METAL

TILE

CONCRETE
MASONRY

STONE TILE

MULTI
MATERIALS

PLASTER &
SOFT
MATERIALS

ASPHALT

ACCESSORIES