

TOOTHED BORE REDUCTION RING

ACCESSORIES

- During use, ensure that the rings are sufficiently wide and do not move.
- For safety reasons, only use rings in which the blade can be clamped by the flanges.
- The ring must never be thicker than the body of the blade : refer to the dimensions indicated on the blades.



SPECIFICATIONS:

REF					
9650.2015.14	1	20	15	1,4	3510789 650046
9650.2016.14	1	20	16	1,4	3510789 650053
9650.3020.14	1	30	20	1,4	3510789 650282
9650.2520.18	1	25	20	1,8	3510789 650077
9650.3015.18	1	30	15	1,8	3510789 650091
9650.3016.18	1	30	16	1,8	3510789 650107

SOLID WOOD

WOOD-DERIVED
PANELS

METAL

TILE

CONCRETE
MASONRY

STONE TILE

MULTI
MATERIALS

PLASTER & SOFT
MATERIALS

ASPHALT

ACCESSORIES

REF					
9650.3018.18	1	30	18	1,8	3510789 650114
9650.3020.18	1	30	20	1,8	3510789 650138
9650.3022.18	1	30	22	1,8	3510789 650145
9650.3025.18	1	30	25	1,8	3510789 650152
9650.3026.18	1	30	25,4	1,8	3510789 650169
9650.3230.18	1	32	30	1,8	3510789 650183
9650.3530.18	1	35	30	1,8	3510789 650206
9650.4030.20	1	40	30	2,0	3510789 650213
9650.4032.20	1	40	32	2,0	3510789 650220
9650.5030.25	1	50	30	2,5	3510789 650237

SOLID WOOD	WOOD-DERIVED PANELS	METAL	TILE	CONCRETE MASONRY	STONE TILE	MULTI MATERIALS	PLASTER & SOFT MATERIALS	ASPHALT	ACCESSORIES
------------	---------------------	-------	------	------------------	------------	-----------------	--------------------------	---------	-------------