THICKNESSER 330 MM


THICKNESSER - PLANER

- Very easy to use transportable machine, ideal for construction sites and workshop.
- Thichnessing table in galvanized steel, with infeed and outfeed extension tables.
- Integrated carrying handles.
- Reversible dust exhaust port with adaptors.
- Jauge de profondeur de passe.





Galvanised steel thicknesser table



Jauge de profondeur de passe

SOLID WOOD | WOOD-DERIVED PANELS | METAL | TILE | CONCRETE MASONRY | STONE TILE | MULTI MATERIALS | PLASTER & SOFT MATERIALS | ASPHALT | ACCESSORIES

RÉF	LORAB330
Conditionnement	1
Colisage	620 x 410 x 475 mm
Garantie	24
Poids net	30,7 kg
Poids brut	33,1 kg
Encombrement machine montee	630 x 560 x 550 mm
Reference pour pieces detachees	210800 (+ N°/ vue éclatée)
Puissance moteur (230 V - 50 Hz)	1500 W (à charbon) - S1
Vitesse de rotation de l'arbre	8500 tr/min
Diamètre de l'arbre	Ø 48 mm
Nombre de fers	2
Dimensions des fers	330 x 12 x 1,5 mm (2 coupes réversibles)
Diamètre sortie d'aspiration	Ø 53 mm avec adaptateurs
Hauteur de travail	Sur établi
Largeur de rabotage	330 mm
Hauteur de rabotage	Jusqu'à 152 mm
Dimensions de la table Rabotage	330 x 235 mm
Profondeur de passe Rabotage	De 0,5 à 3,0 mm
Vitesse d'avance	6 m/min
Pression Acoustique LpA	83,8 dB(A) à vide
Puissance Acoustique LwA	96,8 dB(A) à vide
	3661589102546

ACCESSOIRES

210801

HSS 18% steel - 2 reversible cuts (pair), 333 x 12 x 1,5 mm