

BANDSAW WITH STAND 355 MM

BAND SAW

- Mechanically welded frame, rigid and strong.
- 4-leg stand supplied as a standard equipment.
- 45° tilting cast iron sawing table with upper and lower trunnions in die-cast aluminum.
- Upper and lower blade guides with 3 bearings.
- Adjustment of the blade tension with a knob.
- Cleaning brush on the drivewheel, allowing the blade to have a good grip.
- 2 cutting speeds by changing the position of the belt, depending on the material to be cut.
- 60° adjustable miter gauge, positionable to the right or the left of the table.
- Safety switch on each door.
- Safety switch on each door.



Balanced cast iron flywheels



2 vitesses de coupe, pour bois et métaux non-ferreux

SOLID WOOD

WOOD-DERIVED
PANELS

METAL

TILE

CONCRETE
MASONRY

STONE TILE

MULTI
MATERIALS

PLASTER & SOFT
MATERIALS

ASPHALT

ACCESSORIES

RÉF	SRU355
Conditionnement	1
Colisage	1155 x 380 x 520 mm
Garantie	24
Poids net	84 kg
Poids brut	91 kg
Encombrement machine montee	870 x 750 x 1700 mm
Reference pour pieces detachees	110200 (+ N°/ vue éclatée)
Puissance moteur (230 V - 50 Hz)	900 W - S1
Col de cygne	345 mm
Hauteur de coupe maximale	205 mm
Dimensions de la lame	2490 x 6 - 20 mm
Dimensions de la table Scie	548 x 400 mm
Inclinaison de la table	De 0° à 45°
Hauteur de travail	1020 mm
Diamètre des volants	350 mm
Vitesse de coupe	440 - 900 m/min
Nombre de vitesses	2
Guide d'onglet	± 60°
Diamètre sortie d'aspiration	Ø 100 mm
	3700501700160

SOLID WOOD	WOOD-DERIVED PANELS	METAL	TILE	CONCRETE MASONRY	STONE TILE	MULTI MATERIALS	PLASTER & SOFT MATERIALS	ASPHALT	ACCESSORIES
------------	---------------------	-------	------	------------------	------------	-----------------	--------------------------	---------	-------------

ACCESSOIRES

110201



Mobile wheel kit

SOLID WOOD

WOOD-DERIVED
PANELS

METAL

TILE

CONCRETE
MASONRY

STONE TILE

MULTI
MATERIALS

PLASTER & AMP;
SOFT
MATERIALS

ASPHALT

ACCESSORIES