BANDSAW 600 MM

BAND SAW

400 V

- Mechanically welded frame, rigid and strong.
- Powerful, tough and silent induction motor for cutting solid wood.
- Upper and lower blade guides with 3 cheeks.
- Blade upper guide mounted on a rack and adjustable in height by a crank.
- Well balanced cast iron wheels covered with a rubber tyre for longer blade life.
- Cleaning brush on the drivewheel, allowing the blade to have a good grip.
- Adjustment of the blade tension with a strong handwheel, tension scale is readable through a sighting window on the upper door.
- 60° adjustable miter gauge, positionable on the right of the blade.
- Rip fence with scale on the left side of the blade.
- Emergency stop, steering wheel lock switch.
- Safety switch on each door.
- 2 suction outlets Ø100 mm.





Upper and lower roller blade guide





Table inclinable jusqu'à 30°



Balanced cast iron flywheels



Guide de refente offrant 2 surfaces d'appui

SOLID WOOD | WOOD-DERIVED PANELS | METAL | TILE | CONCRETE MASONRY | STONE TILE | MULTI MATERIALS | PLASTER & SOFT MATERIALS | ASPHALT | ACCESSORIES

RÉF	SRU601T
Conditionnement	1
Colisage	1116 x 774 x 2155 mm
Garantie	24
Poids net	330 kg
Poids brut	350 kg
Encombrement machine montee	1210 x 900 x 2030 mm
Reference pour pieces detachees	111300 (+ N°/vue éclatée)
Puissance moteur (400 V / 50 Hz)	4000 W - S1
Col de cygne	600 mm
Hauteur de coupe maximale	370 mm
Dimensions de la lame	4470 x 10 - 35 mm
Dimensions de la table Scie	700 x 610 mm
Extension de table (LxP)	175 x 595 mm
Inclinaison de la table	0° à +30°
Hauteur de travail	850 mm
Diamètre des volants	610 mm
Vitesse de coupe	1500 m/min
Guide d'onglet	±60°
Diamètre sortie d'aspiration	Ø100 mm (x 2)
Indice de protection	IP54
Pression Acoustique LpA	67,3 dB(A) à vide / 81 dB(A) en charge
Puissance Acoustique LwA	81,9 dB(A) à vide / 96,5 dB(A) en charge
Courant à pleine charge	9A
	3661589112002