

## WOOD LATHE 406 MM

### WOOD LATHE


- Headstock, tailstock, and bed in cast iron for high stability and vibration-free running.
- Bed drilled to be fixed on a stand (optional) or on a workbench.
- Accessories and tools holder on the back of the bench.
- Tailstock with cam lock, live spur MT2 adjustable by handwheel.
- Headstock and tailstock drilled at 10 mm to remove either the headstock spur or the tailstock live center (push-out rod supplied), and to allow the use of a drill bit.
- 200 mm articulated tool rest in cast iron with cam lock.
- Optional bed extension to get a distance between centers of 1025 mm.



12-position indexing



Broche d'entraînement filetée  
m33 x 3.5 mm



6 spindle speeds

SOLID WOOD

WOOD-DERIVED  
PANELS

METAL

TILE

CONCRETE  
MASONRY

STONE TILE

MULTI  
MATERIALS

PLASTER & AMP;  
SOFT  
MATERIALS

ASPHALT

ACCESSORIES

| RÉF                                                                                 | TAB040                                       |
|-------------------------------------------------------------------------------------|----------------------------------------------|
| Conditionnement                                                                     | 1                                            |
| Colisage                                                                            | 850 x 455 x 290 mm                           |
| Garantie                                                                            | 24                                           |
| Poids net                                                                           | 42 kg                                        |
| Poids brut                                                                          | 47 kg                                        |
| Encombrement machine montee                                                         | 990 x 290 x 450 mm                           |
| Reference pour pieces detachees                                                     | 150300 (+ N°/ vue éclatée)                   |
| Puissance moteur (230 V - 50 Hz)                                                    | 580 W - S1                                   |
| Hauteur du banc                                                                     | 190 mm                                       |
| Nombre de vitesses                                                                  | 6                                            |
| Vitesse de rotation                                                                 | 350 - 670 - 1025 - 1500 - 2225 - 3250 tr/min |
| Diviseur                                                                            | 12 positions                                 |
| Distance entre pointes                                                              | 406 mm                                       |
| Diamètre au-dessus du banc                                                          | Ø 305 mm                                     |
| Longueur du support d'outil                                                         | 200 mm                                       |
| Broche d'entrainement                                                               | M33 x 3,5 mm                                 |
| Emmanchement des poupées fixe / mobile                                              | Cône Morse CM2 / CM2                         |
| Perçage de la poupée mobile                                                         | Ø 10 mm                                      |
|  | 3700501706100                                |

SOLID WOOD

WOOD-DERIVED  
PANELS

METAL

TILE

CONCRETE  
MASONRY

STONE TILE

MULTI  
MATERIALS


PLASTER &  
SOFT  
MATERIALS

ASPHALT

ACCESSORIES


## ACCESSOIRES

**150301**



**Stand**

**150302**



**Stand extension**

**150303**



**Bed extension 620 mm**

SOLID WOOD

WOOD-DERIVED  
PANELS

METAL

TILE

CONCRETE  
MASONRY

STONE TILE

MULTI  
MATERIALS

PLASTER &  
SOFT  
MATERIALS

ASPHALT

ACCESSORIES