

## LOG SAW Ø 600 MM

## LOG SAW

- Welded frame offering strength, stability, and maximum resistance to torsion.
- Welded frame offering strength, stability, and maximum resistance to torsion.
- Ground anchoring is possible and recommended.
- Strong and powerful 3500 W induction motor.
- 2 wheels Ø 200 mm and large handle for easy moving.
- Electromagnetic switch.
- Height-adjustable carriage handle for a better comfort.
- Length stop for repetitive cuts, sliding carriage extension for longer logs.



Interlocked top guard and log carriage



Protecteur supérieur avec poignée réglable et griffe de maintien de la bûche

SOLID WOOD

WOOD-DERIVED PANELS

METAL

TILE

CONCRETE MASONRY

STONE TILE

MULTI MATERIALS

PLASTER & SOFT MATERIALS

ASPHALT

ACCESSORIES

RÉF	LOSAB601LC
Conditionnement	1
Colisage	1080 x 830 x 1220 mm
Garantie	24
Poids net	97 kg
Poids brut	123 kg
Encombrement machine montee	1340 x 807 x 1240 mm
Reference pour pieces detachees	300700 (+ N°/ vue éclatée)
Puissance moteur (230 V - 50 Hz)	3500 W - S6 (40%)
Vitesse de rotation	1420 tr/min
Diamètre et alésage de la lame	Ø 600 x 30 mm
Diamètre de bûche minimal/maximal	Ø 80 / 210 mm
Hauteur poignée de chariot	De 850 à 1150 mm
	3661589098900

SOLID WOOD

WOOD-DERIVED  
PANELS

METAL

TILE

CONCRETE  
MASONRY

STONE TILE

MULTI  
MATERIALS

PLASTER &  
SOFT  
MATERIALS

ASPHALT

ACCESSORIES