



## LOG SAW Ø 700 MM

## LOG SAW

- Welded frame offering strength, stability, and maximum resistance to torsion.
- 3-points suspension Cat.1.
- PTO connection (optional shaft connector, not supplied).
- Double belt transmission with safety clutch.
- 2 wheels Ø 210 mm and large handle for easy moving.
- Top cover and pivoting log carriage are interlocked for safe working.
- Height-adjustable carriage handle for a better comfort.
- Length stop for repetitive cuts, sliding carriage extension for longer logs.



Interverrouillage du chariot de coupe et du protecteur supérieur.



Attelage 3 points et entraînement sur prise de force.



Protecteur supérieur avec poignée réglable et griffe de maintien de la bûche

SOLID WOOD

WOOD-DERIVED  
PANELS

METAL

TILE

CONCRETE  
MASONRY

STONE TILE

MULTI  
MATERIALS

PLASTER &  
SOFT  
MATERIALS

ASPHALT

ACCESSORIES

RÉF	LOSAB700
Conditionnement	1
Colisage	1120 x 1000 x 1270 mm
Garantie	24
Poids net	156 kg
Poids brut	170 kg
Encombrement machine montee	1550 x 980 x 1230 mm
Reference pour pieces detachees	301000 (+ N°/ vue éclatée)
Entrainement / Transmission	Cardan / Double courroie
Vitesse de rotation cardan	540 t/min
Puissance tracteur mini	12 kW / 16 CV
Diamètre et alésage de lame	Ø 700 x 30 mm
Vitesse de rotation de lame	1540 t/min
Diamètre de bûche maxi	Ø 240 mm
Largeur du chariot	760 mm
Rallonge de chariot	430 mm
Hauteur poignée de chariot	De 850 à 1150 mm
Puissance sonore	114,5 dB(A)
Incertitude K	4 dB(A)
Courroie	Trapézoïdale B1346
	3661589119513

SOLID WOOD

WOOD-DERIVED  
PANELS

METAL

TILE

CONCRETE  
MASONRY

STONE TILE

MULTI  
MATERIALS

PLASTER &  
SOFT  
MATERIALS

ASPHALT

ACCESSORIES

## ACCESSOIRES

**301001**



PTO shaft connector  
T4-900mm

SOLID WOOD

WOOD-DERIVED  
PANELS

METAL

TILE

CONCRETE  
MASONRY

STONE TILE

MULTI  
MATERIALS

PLASTER & AMP;  
SOFT  
MATERIALS

ASPHALT

ACCESSORIES