

CONCRETE GRINDER 180 MM

CONCRETE GRINDER

- Ergonomic handles for greater comfort when working.
- Soft start with electronic speed variator to adapt the rotation speed to your work.
- Start trigger with lock-on button for continuous work, and power-off protection.
- Toolless detachable brush segment (magnetic) for sanding in corners.
- Integrated exhaust function.
- For sanding, smoothing and dry deburring of building materials (concrete, natural stone, granite, marble, mortar), and for removing adhesive and protective plaster residues.



Toolless detachable brush segment (magnetic)



Système d'aspiration

SOLID WOOD

WOOD-DERIVED PANELS

METAL

TILE

CONCRETE MASONRY

STONE TILE

MULTI MATERIALS

PLASTER & SOFT MATERIALS

ASPHALT

ACCESSORIES

RÉF	POB180
Conditionnement	1
Colisage	440 x 235 x 330 mm
Garantie	24
Poids net	6,920 kg (avec plateau diamanté)
Poids brut	8 kg
Encombrement machine montee	395 x 235 x 295 mm
Reference pour pieces detachees	600400 (+ N°/ vue éclatée)
Puissance moteur (230 V - 50 Hz)	1900 W - S1
Vitesse de rotation	De 500 à 3000 tr/min
Outil adaptable	Plateau Ø 180 x 22,23 mm
Fixation d'outil	Vis M8 x 30 mm
Classe de protection électrique	II
Indice de protection	IPX0
Diamètre sortie d'aspiration	Ø 42 mm
Pression Acoustique LpA	98,2 dB(A) à vide
Puissance Acoustique LwA	109,2 dB(A) à vide
Vibration main-bras	4,8 m/s ²
	3661589107442

SOLID WOOD

WOOD-DERIVED
PANELS

METAL

TILE

CONCRETE
MASONRY

STONE TILE

MULTI
MATERIALS

PLASTER &
SOFT
MATERIALS

ASPHALT

ACCESSORIES