


2-SPEED ELECTRIC MIXER Ø 120 MM

MIXER

- Ergonomic handles with Soft Grip.
- 2-speed gearbox : slow speed and fast speed.
- Electronic speed selector.
- Trigger start with lock-off button to prevent accidental start.
- Application : tile adhesive, plaster, paint, epoxy resin, varnish, mortar and similar substances.
- Mixing capacity : 15 to 25 kg.



Lock-off button



2 modes de vitesse : lent / rapide

SOLID WOOD

WOOD-DERIVED
PANELS

METAL

TILE

CONCRETE
MASONRY


STONE TILE

MULTI
MATERIALS

PLASTER & SOFT
MATERIALS

ASPHALT

ACCESSORIES

RÉF	LOMAX130
Conditionnement	1
Colisage	320 x 270 x 225 mm
Garantie	24
Poids net	4,6 kg
Poids brut	5,7 kg
Reference pour pieces detachees	720800 (+ N°/ vue éclatée)
Puissance moteur (230 V - 50 Hz)	1300 W - S1
Nombre de vitesses	2
Vitesse de rotation 1 (variable)	De 200 à 450 tr/min
Vitesse de rotation 2 (variable)	De 350 à 700 tr/min
Fixation d'outil	Filetage M14
Outil adaptable	Turbine Ø 120 x 600 mm maxi
Classe de protection électrique	II
Indice de protection	IPX0
Surconditionnement (4 machines)	555 x 335 x 465 mm
Poids Brut (4 machines)	23,8 kg
	3661589107312

ACCESSOIRES



Turbine Ø 120 x 590 mm à trois branches

SOLID WOOD

WOOD-DERIVED PANELS

METAL

TILE

CONCRETE MASONRY

STONE TILE

MULTI MATERIALS

PLASTER & SOFT MATERIALS

ASPHALT

ACCESSORIES