

## LONG-REACH DRYWALL SANDER 225 MM

### DRYWALL SANDER

- Brush pad design to absorb dust freely, detachable segment for sanding in corners.
- Powerful motor with soft start function.
- Hook and loop backed sandpaper discs and sponge pad for quick change.
- 4 m suction hose with bayonet swivel connection and adaptor Ø 58 / 35 mm to connect a vacuum cleaner.
- Hose and cable protection device.



Pivoting sanding head



Partie détachable du plateau pour les angles



Hook & loop sponge backing pad

SOLID WOOD

WOOD-DERIVED PANELS

METAL

TILE

CONCRETE MASONRY


STONE TILE

MULTI MATERIALS

PLASTER & SOFT MATERIALS

ASPHALT

ACCESSORIES

RÉF	POG225
Conditionnement	1
Colisage	1530 x 278 x 305 mm
Garantie	24
Poids net	4,7 kg
Poids brut	9,8 kg
Reference pour pieces detachees	225 (+ N°/ vue éclatée)
Puissance moteur (230 V - 50 Hz)	550 W
Longueur du bras	1540 mm
Vitesse de rotation	De 650 à 1600 tr/min
Diamètre de ponçage	Ø 225 mm
Diamètre sortie d'aspiration	Ø 35 mm
Fixation d'outil	Auto-agrippante
Pression Acoustique LpA	91 dB(A)
Puissance Acoustique LwA	102 dB(A)
Vibration main-bras	3,2 m/s <sup>2</sup>
Classe de protection électrique	II
	3661589025166


## ACCESSOIRES

**ABR001**



Carry handle

**ABR002**



Double sided pad  
210 mm 7 holes

**ABR003**



Suction hose with  
bayonet Ø 38-32  
mm, 4 m

SOLID WOOD

WOOD-DERIVED  
PANELS

METAL

TILE

CONCRETE  
MASONRY

STONE TILE

MULTI  
MATERIALS

PLASTER &  
SOFT  
MATERIALS

ASPHALT

ACCESSORIES