

PINCE DE SERRAGE ER 32 - Ø MINI 2 MM - Ø MAXI 20 MM

ACCESORIOS

EXPERT

- Pince de serrage pour mandrin de défonceuse C.N.C.
- Pince en acier traité, rectifiées : doivent être mises en place avec la plus grande attention.
- Tolérance de serrage de 0,5 mm inférieur au diamètre (0,7 mm pour les diamètres de 18 à 20 mm).



CARACTERÍSTICAS:

REF				
890.032.003	1	33 / 3	40	3510785 412495
890.032.004	1	33 / 4	40	3510785 412501
890.032.005	1	33 / 5	40	3510785 412518
890.032.006	1	33 / 6	40	3510785 412525
890.032.008	1	33 / 8	40	3510785 412549
890.032.010	1	33 / 10	40	3510785 412563

MADERA
MACIZA

TABLEROS
DERIVADOS
MADERA

METAL

AZULEJO

HORMIGÓN
MAMPOSTERÍA

PIEDRA TEJA

MULTI
MATERIALES

YESO Y MAT.
BLANDOS

ASFALTO

ACCESORIOS

REF				
890.032.012	1	33 / 12	40	3510785 412570
890.032.014	1	33 / 14	40	3510785 412594
890.032.016	1	33 / 16	40	3510785 412617
890.032.018	1	33 / 18	40	3510785 412624
890.032.020	1	33 / 20	40	3510785 412648

MADERA MACIZA	TABLEROS DERIVADOS MADERA	METAL	AZULEJO	HORMIGÓN MAMPOSTERÍA	PIEDRA TEJA	MULTI MATERIALES	YESO Y MAT. BLANDOS	ASFALTO	ACCESORIOS
------------------	---------------------------------	-------	---------	-------------------------	-------------	---------------------	------------------------	---------	------------