

SIERRA-FRESADORA PARA EL CORTE DE ACERO INOXIDABLE



ACERO INOXIDABLE



HSS
C05

- Dureza 63/64 Hrc.
- Tratamiento vapor.
- Fresas suministradas con orificios de engranaje estándar.
- Se debe respetar la velocidad máxima de 600 rpm.

CARACTERÍSTICAS:

| REF | | | | | | | |
|---------------------|---|-----|----|-----|---|-----|---------------|
| 122CO5.254.2 532 | 1 | 250 | 32 | 2,5 | 4 | 200 | 3661589074843 |
| 122CO5.255.2 532 | 1 | 250 | 32 | 2,5 | 4 | 160 | 3661589074850 |
| 122CO5.274.2 532 | 1 | 275 | 32 | 2,5 | 4 | 220 | 3661589074867 |
| 122CO5.275.2 532 | 1 | 275 | 32 | 2,5 | 4 | 180 | 3661589074874 |
| 122CO5.276.2 532 | 1 | 275 | 32 | 2,5 | 4 | 140 | 3661589074881 |
| 122CO5.274.2 540 | 1 | 275 | 40 | 2,5 | 4 | 220 | 3661589074898 |
| 122CO5.275.2 540 | 1 | 275 | 40 | 2,5 | 4 | 180 | 3661589074904 |

MADERA
MACIZA

TABLEROS
DERIVADOS
MADERA

METAL

AZULEJO

HORMIGÓN
MAMPOSTERÍA








PIEDRA TEJA

MULTI
MATERIALES

YESO Y MAT.
BLANDOS

ASFALTO

ACCESORIOS

| REF |  |  |  |  |  |  |  |
|---------------------|---|---|---|---|---|---|---|
| 122CO5.276.2 540 | 1 | 275 | 40 | 2,5 | 4 | 140 | 3661589074911 |
| 122CO5.304.2 532 | 1 | 300 | 32 | 2,5 | 4 | 220 | 3661589074928 |
| 122CO5.305.2 532 | 1 | 300 | 32 | 2,5 | 4 | 180 | 3661589074935 |
| 122CO5.306.2 532 | 1 | 300 | 32 | 2,5 | 4 | 140 | 3661589074942 |
| 122CO5.314.2 532 | 1 | 315 | 32 | 2,5 | 4 | 240 | 3661589074959 |
| 122CO5.315.2 532 | 1 | 315 | 32 | 2,5 | 4 | 200 | 3661589074966 |
| 122CO5.316.2 532 | 1 | 315 | 32 | 2,5 | 4 | 160 | 3661589074973 |

MADERA
MACIZA

TABLEROS
DERIVADOS
MADERA

METAL

AZULEJO

HORMIGÓN
MAMPOSTERÍA

PIEDRA TEJA

MULTI
MATERIALES

YESO Y MAT.
BLANDOS

ASFALTO

ACCESORIOS