

PINCE DE SERRAGE GRS 25 - 462 E - Ø MINI 3 MM - Ø MAXI 25 MM

ACCESSORI



EXPERT

- Pince de serrage pour mandrin de défonceuse C.N.C.
- Pince en acier traité, rectifiées : doivent être mises en place avec la plus grande attention.
- Tolérance de serrage de 0,5 mm inférieur au diamètre.

CARATTERISTICHE:

REF				
890.462.006	1	35 / 6	52	3510785 412839
890.462.008	1	35 / 8	52	3510785 412846
890.462.010	1	35 / 10	52	3510785 412853
890.462.012	1	35 / 12	52	3510785 412860
890.462.014	1	35 / 14	52	3510785 412877
890.462.016	1	35 / 16	52	3510785 412884

LEGNO
MASSICCIO

PANNELLI
DERIVATI
LEGNO

METALLO

PIASTRELLA

CALCESTRUZZO
MURATURA

PIETRA TEGOLA

MULTI
MATERIALI

GESSO E MAT.
TENERI

ASFALTO

ACCESSORI

REF				
890.462.018	1	35 / 18	52	3510785 412891
890.462.020	1	35 / 20	52	3510785 412907
890.462.025	1	35 / 25	52	3510785 412914