

PINCE DE SERRAGE ER 40 - Ø MINI 3 MM - Ø MAXI 25 MM

ACCESSOIRES

EXPERT

- Pincas de serrage pour mandrin de défonceuse C.N.C.
- Pincas en acier traité, rectifiées : doivent être mises en place avec la plus grande attention.
- Tolérance de serrage de 0,7 mm inférieur au diamètre.



CARACTERISTIQUES :

REF				
890.040.006	1	41 / 6	46	3510785 412686
890.040.008	1	41 / 8	46	3510785 412693
890.040.010	1	41 / 10	46	3510785 412716
890.040.012	1	41 / 12	46	3510785 412730
890.040.014	1	41 / 14	46	3510785 412747
890.040.016	1	41 / 16	46	3510785 412754

BOIS MASSIF

PANNEAUX
DÉRIVÉS BOIS

MÉTAL

CARRELAGE

BÉTON
MAÇONNERIE

PIERRE TUILE

MULTI
MATÉRIAUX

PLÂTRE ET
MATÉRIAUX
TENDRES

ASPHALTE

ACCESSOIRES

REF				
890.040.018	1	41 / 18	46	3510785 412761
890.040.020	1	41 / 20	46	3510785 412778
890.040.025	1	41 / 25	46	3510785 412785

BOIS MASSIF

PANNEAUX
DÉRIVÉS BOIS

MÉTAL

CARRELAGE

BÉTON
MAÇONNERIE

PIERRE TUILE

MULTI
MATÉRIAUX

PLÂTRE ET
MATÉRIAUX
TENDRES

ASPHALTE

ACCESSOIRES