

MEULE VITRIFIÉE BLANCHE

- Meulage des aciers rapides.
- Meule plate vitrifiée en corindon supérieur 22A.
- Rotation : 35 m/s.
- Livrée avec bagues de réduction 32/25,4 - 25,4/20 - 20/16 - 16/12,7 (sauf meule Ø 125 mm).



MÉTAL



OUTIL EN ACIER RAPIDE

EN12413



CARACTERISTIQUES :

REF							
12017	1	125	5350	20	20	60	3510780 120173
15014	1	150	4500	32	20	46	3510780 150149
15016	1	150	4500	32	20	60	3661589 006912
15516	1	150	4500	32	25	60	3510780 155168
22014	1	200	3350	32	20	46	3510780 220149
22016	1	200	3350	32	20	60	3510780 220163

BOIS MASSIF

PANNEAUX
DÉRIVÉS BOIS

MÉTAL

CARRELAGE

BÉTON
MAÇONNERIE








PIERRE TUILE

MULTI
MATÉRIAUX

PLÂTRE ET
MATÉRIAUX
TENDRES

ASPHALTE

ACCESSOIRES

REF							
22514	1	200	3350	32	25	46	3510780 225144
22516	1	200	3350	32	25	60	3510780 225168

BOIS MASSIF

PANNEAUX
DÉRIVÉS BOIS

MÉTAL

CARRELAGE

BÉTON
MAÇONNERIE

PIERRE TUILE

MULTI
MATÉRIAUX

PLÂTRE ET
MATÉRIAUX
TENDRES

ASPHALTE

ACCESSOIRES