

PINCE DE SERRAGE ER 40 - Ø MINI 3 MM - Ø MAXI 25 MM



EXPERT

- Pincas de serrage pour mandrin de défonceuse C.N.C.
- Pincas en acier traité, rectifiées : doivent être mises en place avec la plus grande attention.
- Tolérance de serrage de 0,7 mm inférieur au diamètre.

KENMERKEN:

| REF | | | | | |
|-------------|---|---------|----|---|-------------------|
| 890.040.006 | 1 | 41 / 6 | 46 | - | 3510785 412686 |
| 890.040.008 | 1 | 41 / 8 | 46 | - | 3510785 412693 |
| 890.040.010 | 1 | 41 / 10 | 46 | - | 3510785 412716 |
| 890.040.012 | 1 | 41 / 12 | 46 | - | 3510785 412730 |
| 890.040.014 | 1 | 41 / 14 | 46 | - | 3510785 412747 |
| 890.040.016 | 1 | 41 / 16 | 46 | - | 3510785 412754 |

MASSIEF HOUT

HOUTCOMPOSITE
PLATEN

METAAL

TEGEL

BETON
METSSELWERK

STEEN TEGEL

MULTI
MATERIALEN

GIPS & ZACHTE
MATERIALEN

ASFALT

ACCESSOIRES

| REF |  |  |  |  |  |
|-------------|---|---|---|---|---|
| 890.040.018 | 1 | 41 / 18 | 46 | - | 3510785 412761 |
| 890.040.020 | 1 | 41 / 20 | 46 | - | 3510785 412778 |
| 890.040.025 | 1 | 41 / 25 | - | 46 | 3510785 412785 |